CITY OF O'FALLON PROPERTY MAINTENANCE INSPECTION CHECKLIST __ Address: Residence Type: 1 Story/Garage/Basement Apartment 2 Story/Garage/Basement Condo Bi/Tri-level/Garage Mobile Home Duplex/1 Story/2 Story Garage/Basement INTERIOR Interior ceilings and walls in good repair(PM305.3):___ Enclosed space under stairs has coverage of minimum ½" drywall(IRC302.7):_____ (Working)Smoke detectors at every level, within 15ft of bedrooms and inside each bedroom_____ (Working)CO detector within 15 ft of each bedroom: ___Window hardware and glass in good working order(PM 304.13.2):_____ _Window screens maintained and in good shape(PM304.14):_____ 3 wire electrical systems properly grounded(PM605.1): 2 wire electrical systems is GFCI protected or 2 prong outlets installed(PM605.1): ____Hot/neutral reverse at receptacles(PM605.1):____ Extension cords safely used for temporary power(PM604.3): Electric cover plates installed(PM604.3/605.2):___ Fuse/breaker box clear of defects and circuits are labeled(PM604.3/605.1):_____ ____Laundry receptacles GFCI or single use and grounded if within 6 ft of a sink(PM605.1/NEC):____ Heat/Wat.Heat units properly vented and 3 screws per joint(PM603.2/603.4/Ameren):_____ ____Adequate combustion airspace(PM603.5,IFGC404.12):_____ ___Gas shut-off at all appliances(PM603.4):__ Water heater discharge pipe min ³/₄", metal, no threads and stops within 6" of floor(PM505.4) Ingress and Egress clear path to the outside. Doors to the exterior operable(PM702.1/702.4) Exterior door locks operable (thumb latch, single cylinder)(PM304.15/702.3)_____ **KITCHEN** Receptacles GFCI protected (All at the countertops, exc. desk areas)(NEC210.8(A):_____ Garbage disposal functions /installed correctly with Romex connector(PM504.1):_____ Water on, no leaks(PM504.1): **BATHROOMS** _All receptacles GFCI protected(NEC210.8A):_____ Water on, no leaks(PM504.1): Vent to outside (Or window)(PM403.2): **GARAGE** Garage Receptacles GFCI protected (within 6 ft zone excluding ceiling)(NEC210.8A):_____ Solid core wood, rated or metal door between living area and garage(IRC302.5):_____ ½" drywall separation between living area and garage applied to garage side(IRC302.6):______ ___Drywall to roof sheathing line or garage ceiling, covered with ½" drywall(IRC302.6):_____ Garage door safety sensors, if required, operational:__ **EXTERIOR** House numbers visible and 4" tall x ½" stroke min(PM304.3): Outside appearance maintained(PM304.1):_____ Gutters/downspouts in good repair & discharge properly(PM304.7)_____ ___Foundation/exterior walls in good repair(PM304.5/304.6):____ ____Handrails and guard rails secure and code compliant(PM305.5/306.1/307.1):____ Accessory structures in good repair(PM302.7): Decks, porches, balconies maintained(PM304.2/304.10): ___Chimneys in good repair(PM304.11):__ Ext. receptacles GFCI protected (Readily accessible only)(NEC210.8(A)): Sump pump discharges to outside (not the sanitary sewer system)/not a nuisance(Ord.818/3154):_ Driveway/sidewalk in good repair(PM302.3):

Bedrooms				Net Area
- Master or #1 - Size	Meets Egress	Y/N		
- #2 - Size	Meets	Egress Y/I	N	
- #3 - Size	Meets	Egress Y/I	N	
- #4 - Size	Meets	Egress Y/I	N	
- #5 - Size	Meets	Egress Y/I	N	
- Two outlets in each bedroom(P	M605.2): (1)	_(2)(3)	(4)	(5)
- Open-able windows(PM304.13	.2): (1)(2)	(3)	(4)	
- Smoke detector(PM704.1/704.2/	704.4): (1)	(2)(2)	3)(4)	(5)
- Interconnected?				
- Carbon Monoxide detector with	nin 15ft of bedroom	ns (if needed)_		
Basement Sleeping Rooms				Net Area
- #1 - Size		-	Y/N	l l
- #2 - Size	Meets	Egress	Y/N	
- Smoke detector(PM704.1/704.2/				'
- Carbon Monoxide detector with	nin 15ft of bedroom	is (if needed)		
SPAS/POOLS : (PM303, NEC a			ellaneous: Addi	tional GFCI
IRC Appe	ndix G)	•	irements(NEC):	go hothtubo(690.71)
Barrier- Electric-			•	ge bathtubs(680.71) asement(210.8A)
Alarms-			Bar sinks(210	
1111111111111111111111111111111111			Dur 5111115(21)	0.011)
NOTES:				
Inspected by:		Date:		
	Approved	Not Approved		
CPTED Inspection Pass:	Yes	No		_N/A
Occupancy Load:				