City of O'Fallon - Water Meter and Tap Sizing

Builder/Developer:	_
--------------------	---

Address:

Lot # Subdivision

					ues in Wat re Units (W					
	Fixture	Occupancy	Type of Supply Control	Cold	Hot	Total Value for Fixture	x	No. of Fixtures	=	Total WSFUs per Fixture Type
1	Water Closet	Public	Flush Valve	10	-	10	х		=	
2	Water Closet	Public	Flush Tank	5	-	5	Х		=	
3	Urinal	Public	1" Flush Valve	10	-	10	Х		=	
4	Urinal	Public	3/4" Flush Valve	5	-	5	Х		=	
5	Urinal	Public	Flush Tank	3	-	3	Х		=	
6	Lavatory	Public	Faucet	1.5	1.5	2	Х		=	
7	Bathtub	Public	Faucet	3	3	4	Х		=	
8	Shower Head	Public	Mixing Valve	3	3	4	Х		=	
9	Service Sink	Offices, etc.	Faucet	2.25	2.25	3	х		=	
10	Kitchen Sink	Hotel/Restaurant	Faucet	3	3	4	Х		=	
11	Drinking Fountain	Offices, etc.	3/8" Valve	0.25	-	0.25	Х		=	
12	Water Closet	Private	Flush Valve	6	-	6	Х		=	
13	Water Closet	Private	Flush Tank	3	-	3	Х		=	
14	Lavatory	Private	Faucet	0.75	0.75	1	Х		=	
15	Bathtub	Private	Faucet	1.5	1.5	2	Х		=	
16	Shower Stall	Private	Mixing Valve	1.5	1.5	2	Х		=	
17	Kitchen Sink	Private	Faucet	1.5	1.5	2	Х		=	
18	Laundry Trays (1 to 3)	Private	Faucet	2.25	2.25	3	Х		=	
19	Combination Fixture	Private	Faucet	2.25	2.25	3	Х		=	
20	Dishwashing Machine	Private	Automatic	-	1	1	Х		=	
21	Laundry Machine (8 lb)	Private	Automatic	1.5	1.5	2	Х		=	
22	Laundry Machine (8 lb)	Public/General	Automatic	2.25	2.25	3	Х		=	
23	Laundry Machine (16 lb)	Public/General	Automatic	3	3	4	Х		=	
					-		NSF uildi	Us for	=	
rigation \$	System Demand:	gpm_ Consult Table N, O, and P for Meter and			Sizing.	Size of Meter:		leter:		
	Applicant Signature:					Size of S	Serv	ice Llne:		
	Printed Name and Date:					Fire S	Spri	nkler:		Circle One 'es No
	Phone Number:						- 1-1-			03 110

77 ILLINOIS ADMINISTRATIVE CODE, PART 890 ILLINOIS PLUMBING CODE (02/04)

Section 890.APPENDIX A PLUMBING MATERIALS, EQUIPMENT. USE RESTRICTIONS AND APPLICABLE STANDARDS

Table N Water Supply Fixture Units (W.S.F.U.) for a Supply System with Flush Tanks

Water Supply Fixture Units (W.S.F.U.) for a

$\begin{array}{c c c c c c c c c c c c c c c c c c c $	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	
4 3 $\frac{1}{2}$ " 8.7 4.2 $5/8$ " 6 5 $\frac{1}{2}$ " 22.5 7.0 $5/8$ " 8 6.5 $3/4$ " 6.3 4.3 $5/8$ " 10 8 $3/4$ " 9.0 5.4 $3/4$ " 12 9.2 $3/4$ " 11.5 6.1 $3/4$ " 14 10.4 $3/4$ " 15.0 6.9 $3/4$ " 16 11.6 $3/4$ " 18.0 7.7 $3/4$ " 20 14 1" 7.2 5.6 $3/4$ " 20 14 1" 7.2 5.6 $3/4$ " 30 20 1" 13.6 8.0 1" 35 22.5 1 $1/4$ " 7.0 6.3 1" 40 25 1 $1/4$ " 7.0 6.3 1" 45 27 1 $1/4$ " 8.2 6.9 1" 50 29 1 $1/4$ " 9.5 7.4 1" 60 32 1	<u> </u>
4 3 $\frac{1}{2}$ " 8.7 4.2 $5/8$ " 6 5 $\frac{1}{2}$ " 22.5 7.0 $5/8$ " 8 6.5 $3/4$ " 6.3 4.3 $5/8$ " 10 8 $3/4$ " 9.0 5.4 $3/4$ " 12 9.2 $3/4$ " 11.5 6.1 $3/4$ " 14 10.4 $3/4$ " 15.0 6.9 $3/4$ " 16 11.6 $3/4$ " 18.0 7.7 $3/4$ " 20 14 1" 7.2 5.6 $3/4$ " 20 14 1" 7.2 5.6 $3/4$ " 30 20 1" 13.6 8.0 1" 35 22.5 1 $1/4$ " 7.0 6.3 1" 40 25 1 $1/4$ " 7.0 6.3 1" 45 27 1 $1/4$ " 8.2 6.9 1" 50 29 1 $1/4$ " 9.5 7.4 1" 60 32 1	
6 5 $\frac{1}{2}$ " 22.5 7.0 5/8" 8 6.5 3/4" 6.3 4.3 5/8" 10 8 3/4" 9.0 5.4 3/4" 12 9.2 3/4" 11.5 6.1 3/4" 14. 10.4 3/4" 15.0 6.9 3/4" 16 11.6 3/4" 18.0 7.7 3/4" 20 14 1" 7.2 5.6 3/4" 20 14 1" 7.2 5.6 3/4" 30 20 1" 13.6 8.0 1" 35 22.5 1 1/4" 5.8 5.7 1" 40 25 1 1/4" 7.0 6.3 1" 45 27 1 1/4" 8.2 6.9 1" 50 29 1 1/4" 9.5 7.4 1" 60 32 1 1/2" 5.0 5.8 1 1/2" 70 35 1 <	
8 6.5 $3/4^*$ 6.3 4.3 $5/8^*$ 10 8 $3/4^*$ 9.0 5.4 $3/4^*$ 12 9.2 $3/4^*$ 11.5 6.1 $3/4^*$ 14 10.4 $3/4^*$ 15.0 6.9 $3/4^*$ 14 10.4 $3/4^*$ 18.0 7.7 $3/4^*$ 20 14 1^* 7.2 5.6 $3/4^*$ 20 14 1^* 7.2 5.6 $3/4^*$ 25 17 1^* 10.0 6.6 $3/4^*$ 30 20 1^* 13.6 8.0 1^* 35 22.5 $11/4^*$ 5.8 5.7 1^* 40 25 $11/4^*$ 7.0 6.3 1^* 45 27 $11/4^*$ 8.2 6.9 1^* 50 29 $11/4^*$ 9.5 7.4 1^* 60 32 $11/2^*$ 5.0 5.8 $11/2^*$ </td <td></td>	
10 8 $3/4"$ 9.0 5.4 $3/4"$ 12 9.2 $3/4"$ 11.5 6.1 $3/4"$ 14 10.4 $3/4"$ 15.0 6.9 $3/4"$ 16 11.6 $3/4"$ 18.0 7.7 $3/4"$ 20 14 1" 7.2 5.6 $3/4"$ 20 14 1" 7.2 5.6 $3/4"$ 20 14 1" 7.2 5.6 $3/4"$ 20 14 1" 7.2 5.6 $3/4"$ 20 14 1" 7.2 5.6 $3/4"$ 20 14 1" 7.2 5.6 $3/4"$ 30 20 1" 13.6 8.0 $1"$ 35 22.5 1 $1/4"$ 7.0 6.3 $1"$ 40 25 1 $1/4"$ 7.0 6.3 $1"$ 45 27 1 $1/4"$ 9.5 7.4 $1"$ 60 32 <td></td>	
12 9.2 $3/4^*$ 11.5 6.1 $3/4^*$ 14. 10.4 $3/4^*$ 15.0 6.9 $3/4^*$ 16 11.6 $3/4^*$ 18.0 7.7 $3/4^*$ 20 14 1" 7.2 5.6 $3/4^*$ 20 14 1" 7.2 5.6 $3/4^*$ 20 14 1" 7.2 5.6 $3/4^*$ 20 14 1" 7.2 5.6 $3/4^*$ 30 20 1" 13.6 8.0 1" 35 22.5 1 $1/4^*$ 5.8 5.7 1" 40 25 1 $1/4^*$ 7.0 6.3 1" 45 27 1 $1/4^*$ 8.2 6.9 1" 50 29 1 $1/4^*$ 9.5 7.4 1" 60 32 1 $1/2^*$ 5.0 5.8 1 $1/2^*$ 70 35 1 $1/2^*$ 6.2 6.4 1 $1/2^*$	
14. 10.4 $3/4^*$ 15.0 6.9 $3/4^*$ 16 11.6 $3/4^*$ 18.0 7.7 $3/4^*$ 20 14 1" 7.2 5.6 $3/4^*$ 20 14 1" 7.2 5.6 $3/4^*$ 20 14 1" 7.2 5.6 $3/4^*$ 25 17 1" 10.0 6.6 $3/4^*$ 30 20 1" 13.6 8.0 1" 35 22.5 1 $1/4^*$ 5.8 5.7 1" 40 25 1 $1/4^*$ 7.0 6.3 1" 45 27 1 $1/4^*$ 8.2 6.9 1" 50 29 1 $1/4^*$ 9.5 7.4 1" 60 32 1 $1/2^*$ 5.0 5.8 1 $1/2^*$ 70 35 1 $1/2^*$ 6.2 6.4 1 $1/2^*$	
16 11.6 $3/4"$ 18.0 7.7 $3/4"$ 20 14 1" 7.2 5.6 $3/4"$ 25 17 1" 10.0 6.6 $3/4"$ 30 20 1" 13.6 8.0 1" 35 22.5 .1 $1/4"$ 5.8 5.7 1" 40 25 1 $1/4"$ 7.0 6.3 1" 45 27 1 $1/4"$ 8.2 6.9 1" 50 29 1 $1/4"$ 9.5 7.4 1" 60 32 1 $1/2"$ 5.0 5.8 1 $1/2"$ 70 35 1 $1/2"$ 6.2 6.4 1 $1/2"$	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	
30 20 1° 13.6 8.0 1° 35 22.5 $11/4^{\circ}$ 5.8 5.7 1° 40 25 $11/4^{\circ}$ 7.0 6.3 1° 45 27 $11/4^{\circ}$ 8.2 6.9 1° 50 29 $11/4^{\circ}$ 9.5 7.4 1° 60 32 $11/2^{\circ}$ 5.0 5.8 $11/2^{\circ}$ 70 35 $11/2^{\circ}$ 6.2 6.4 $11/2^{\circ}$	
35 22.5 1 1/4" 5.8 5.7 1" 40 25 1 1/4" 7.0 6.3 1" 45 27 1 1/4" 8.2 6.9 1" 50 29 1 1/4" 9.5 7.4 1" 60 32 1 1/2" 5.0 5.8 1 1/2" 70 35 1 1/2" 6.2 6.4 1 1/2"	
40 25 1 1/4" 7.0 6.3 1" 45 27 1 1/4" 8.2 6.9 1" 60 29 1 1/4" 9.5 7.4 1" 60 32 1 1/2" 5.0 5.8 1 1/2" 70 35 1 1/2" 6.2 6.4 1 1/2"	
40 25 1 1/4" 7.0 6.3 1" 45 27 1 1/4" 8.2 6.9 1" 50 29 1 1/4" 9.5 7.4 1" 60 32 1 1/2" 5.0 5.8 1 1/2" 70 35 1 1/2" 6.2 6.4 1 1/2"	
50 29 1 1/4" 9.5 7.4 1" 60 32 1 1/2" 5.0 5.8 1 1/2" 70 35 1 1/2" 6.2 6.4 1 1/2"	
60 32 1 1/2" 5.0 5.8 1 1/2" 70 35 1 1/2" 6.2 6.4 1 1/2"	
70 35 1 1/2" 6.2 6.4 1 1/2"	
90 41 1 1/2" 8.0 7.5 1 1/2"	
100 43.5 1 1/2" 8.7 7.8 2"	
120 48 2" 2.7 5.0 2"	
140 52.5 2" 3.1 5.4 2"	
160 57 2" 3.6 5.8 2"	
180 61 2" 3.9 6.1 2"	
200 65 2" 4.5 6.6 2"	
225 70 2" 5.2 7.1 2"	
250 75 2" 6.0 7.7 3"	
275 80 2 ½" 2.6 5.5 3"	
300 85 2 ½" 2.9 5.8 3"	
350 95 2 ½ " 3.5 6.5 3"	
400 105 2 ½* 4.2 7.1 3*	
450 115 2 ½° 5.0 8.0 3°	

77 ILLINOIS ADMINISTRATIVE CODE, PART 890 ILLINOIS PLUMBING CODE (02/04)

Section 890.APPENDIX A PLUMBING MATERIALS, EQUIPMENT, USE RESTRICTIONS AND APPLICABLE STANDARDS

Table N Water Supply Fixture Units (W.S.F.U.) for a Supply System with Flush Tanks

Water Supply Fixture Units (W.S.F.U.) for a

	Demand	Pipe Size	Pressure Loss		Meter Size
W.S.F.U.	(GPM)	(Inches)	(PSI/100' of Pipe)	(Ft./Sec.)	(Inches)
500	125	3"	2.3	5.9 🗉	3"
600	145	3"	3.1	6,8	4"
750	170	3"	4.0	8.0	4"
1000	208	4"	1.5	5.7	4"
1250	240	4"	1.9 🔹	6.4	4"
1500	267	4"	2.3	7.0	4"
1750	294	4×	2.8	7.8	4"
2000	320	6"	0.36	3.7	6"

~

Agency Notes: Where a unit of local government or the community public water supply does not require separate water service lines for irrigation or similar systems that are likely to impose continuous demands (e.g., lawn sprinkler or air conditioning systems), the following rule applies: estimate the continuous demand (in gallons per minute) for such outlets/systems separately from the intermittent demand from the above fixtures, and add this amount to the demand of the fixtures (in gallons per minute).

Meter and meter yoke sizes shown in this table shall apply only to those juriadictions or governmental units where local ordinances or community public water supply requirements do not prescribe specific sizes of meters and/or meter yokes. Where local ordinances or community public water supply requirements cover such sizing, those requirements shall be followed.

(Source: Amended at 28 III. Reg. 4215, effective February 18, 2004)

77 ILLINOIS ADMINISTRATIVE CODE, PART 890 ILLINOIS PLUMBING CODE (02/04)

Section 890.APPENDIX A PLUMBING MATERIALS, EQUIPMENT, USE RESTRICTIONS AND APPLICABLE STANDARDS

Table O	Water Supply Fixture Units (W.S.F.U.) for a
	Supply System with Flushometer

Water Supply Fixture Units (W.S.F.U.) for a

7

Supply System with Flushometer							
W.S.F.U.	Demand (GPM)	Pipe Size (Inches)	Pressure Loss (PSI/100' of Pipe)	Velocity (Ft./Sec.)	Meter Size (Inches)		
10	27	1 1/4"	8.3	6.8	3/4"		
12	28.6	1 1/4"	9.2	7.2	3/4*		
14	30.2	1 1/4"	10.0	7.9	3/4"		
16	31.8	1 1/4"	11.0 *	8.0	3/4*		
20	35	1 1/2"	6.0	6.4	3/4"		
25	38	1 1/2"	7.0	6.9	1"		
30	41	1 1/2"	8.0	7.4	i.		
35	43.8	1 1/2"	8.8	8.0	1.		
40	46.5	2*	2.5	4.7	i"		
45	49	2"	2.7	5.1	1"		
50	51.5	2"	2.9	5.4	1 1/2"		
60	55	2"	3.4	5.8	1 1/2"		
70	58.5	2"	3.7	6.0	1 1/2"		
80	62	2"	4.0	6.2	1 1/2"		
90	64.8	2"	4.6	6.5	1 1/2'		
100	67.5	2"	5.0	6.8	1 1/2"		
120	72.5	2"	5.6	7.2	2"		
140	77.5	2'	6.3	8.0	2*		
160	82.5	2 1/2"	2.7	5.7	2"		
180 -	87	2 ½"	3.0	6.1	° 2'		
200	91.5	2 1/2"	3.4	6.4	2"		
225	97	2 1/2"	3.7	6.8	2"		
250	101	2 ½"	4.0	7.1	3"		
275	106	2 ½	4.2	7.3	3"		
300	110	2 1/2"	4.6	7.6	3"		
350	119	3"	2.1	5.5	3"		
400	126	3"	2.3	5.9	3"		
450	138	3"	2.7	6.3	3"		
500	145	3"	3.0	6.8	3"		
600	160	3"	3.6	7.4	4"		

77 ILLINOIS ADMINISTRATIVE CODE, PART 890 ILLINOIS PLUMBING CODE (02/04)

Section 890.APPENDIX A PLUMBING MATERIALS, EQUIPMENT, USE RESTRICTIONS AND APPLICABLE STANDARDS

Table O Water Supply Fixture Units (W.S.F.U.) for a Supply System with Flushometer

Water Supply Fixture Units (W.S.F.U.) for a Supply System with Flushometer (Continued)

<u>W.S.F.U.</u>	Demand (GPM)		Pressure Loss (PSI/100' of Pipe)	Velocity (Ft./Sec.)	Meter Size (Inches)
750	178	4"	1.1	4.7	4*
1000	208	4"	1.5	5.6	4"
1250	240	4"	1.9	6.4	4"
1500	267	4"	2.3	7.0	4"
1750	294	4"	2.8	7.8	4"
2000	321	6"	0.4	3.7	6"

Agency Notes: Where a unit of local government or the community public water supply does not require separate water service lines for irrigation or similar systems that are likely to impose continuous demands (e.g., lawn sprinkler or air conditioning systems), the following rule applies: estimate the continuous demand (in gallons per minute) for such outlets/systems separately from the intermittent demand from the above fixtures, and add this amount to the demand of the fixtures (in gallons per minute).

Meter and meter yoke sizes shown in this table shall apply only to those jurisdictions or governmental units where local ordinances or community public water supply requirements do not prescribe specific sizes of meters and/or meter yokes. Where local ordinances or community public water supply requirements cover such sizing, those requirements shall be followed.

(Source: Amended at 28 III. Reg. 4215, effective February 18, 2004)

77 ILLINOIS ADMINISTRATIVE CODE. PART 890 ILLINOIS PLUMBING CODE (02/04)

Section 890.APPENDIX A PLUMBING MATERIALS, EQUIPMENT, USE RESTRICTIONS AND APPLICABLE STANDARDS

TABLE P Demand at Individual Water Outlets

Demand at Individual Water Outlets

Type Of Outlet	Demand (g.p.m.)
Ordinary Lavatory Faucet	2.0
Self Closing Lavatory Faucet	2.5
Sink Faucet, 3/8" or ½"	4.5
Sink Faucet, 3/4"	6.0
Bath Faucet, ½*	5.0
Shower Head, ½"	5.0
Laundry Faucet, ½"	5.0
Ballcock in Water Closet Flush Tank	3.0
1" Flush Valve (25 psi flow pressure)	35.0
1" Flush Valve (15 psi flow pressure)	27.0
3/4" Flush Valve (15 psi flow pressure)	15.0
Drinking Fountain Jat	0.75
Dishwashing Machine (domestic)	4.0
Laundry Machine (8 to 16 pounds)	4.0
Aspirator (operating room or laboratory)	2.5
(Source: Amended at 28 III. Reg. 4215, effectiv	e February 18, 2004)

77 ILLINOIS ADMINISTRATIVE CODE, PART 890 ILLINOIS PLUMBING CODE (02/04)

Section 890.APPENDIX A PLUMBING MATERIALS, EQUIPMENT, USE RESTRICTIONS AND APPLICABLE STANDARDS

Table Q Allowance in Equivalent Length of Pipe for Friction Loss in Valves and Fittings

> Allowance in Equivalent Length of Pipe for Friction Loss in Valves and Fittings

The following applies to all types of material approved for potable water distribution:

	Eg	<u>vivalent</u>	Feet	of Pipe	<u>for Va</u>	rious F	lipes Si	<u>zes</u>
Valve or Fitting	%"	3/4"	1"	1 1/4"	1 1/2'	' 2"	2 %	' 3"
45° ell (wrought)	0.5	0.5	1.0	1.0	2.0	2.0	3.0	4.0
90° eli (wrought)	0.5	1.0	1.0	2.0	2.0	2.0	2.0	3.0
Tee, Run (wrought)	0.5	0.5	0.5	0.5	1.0	1.0	2.0	1
Tee, Branch (wrought)	1.0	2.0	3.0	4.0	5.0	7.0	9.0	-
45° ell (cast)	0.5	1.0	2.0	2.0	3.0	5.0	8.0	11.0
90° ell (cast)	1.0	2.0	4.0	5.0	8.0	11.0	14.0	18.0
Tee, Run (cast)	0.5	0.5	0.5	1.5	1.0	2.0	2.0	2.0
Tee, Branch (cast)	2.0	3.0	5.0	7.0	9.0	12.0	16.0	20.0
Compression Stop	13.0	21.0	30.0	ž	×	۲	-	
Globe Valve		×	-	53.0	66.0	90.0	а Это	
Gate Valve	-		1.0	1.0	2.0	2.0	2.0	2.0

(Appendix A/Page - 56)